
















TILES ACOUSTIC FLOORING FELT

TECHNICAL INFORMATION

	Use classification	ISO 10874	33 Heavy commercial	32 General commercial
	Weight	ISO 8543	3,3-3,5 kg/m ²	3,3-3,5 kg/m ²
	Thickness	ISO 1765	5,0-5,2 mm	5,1 mm
	Tile dimension	EN 994	500 x 500 mm, 12 pcs/box	500 x 500 mm, 12 pcs/box
	Impact sound insulation*	EN ISO 10140	21 dB	22 dB
	Castor Chair	EN 985	Intensive use	Intensive use
	Body Voltage	EN 1815**	Fulfilled	Fulfilled
	Thermal resistance	ISO 8302	Suitable for underfloor heating	Suitable for underfloor heating
	Airborne sound absorption*	EN ISO 354	0,15	0,15
	Colour fastness to light*	EN ISO 105-B02	8	8
	Dimension stability	EN 986	Fulfilled	Fulfilled
	Anti slip property	A54586:2013	R10	R10
	Anti slip property	A54586:2013	P2	P3
	Dynamic coefficient of friction	EN 13893	> 0,3	> 0,3
	Reaction to fire	EN 13501-1	B _{fl} -s1	B _{fl} -s1
	Critical radiant flux	ISO9239.1	6.7 kw/m ²	7.4 kw/m ²
	Smoke density	ISO.9239.1	205% min	189% min.

LIFE CYCLE ANALYSIS
FOR RAW MATERIALS



INDOOR AIR



OTHER



Collections 33 Heavy commercial: Graphic, Silence, Diversity, Create, Artisan, Elements, Bolon By You, Bolon By Jean Nouvel Design, Missoni Home

Collections 32 General commercial: Botanic, Ethnic, Bkb, Now, Flow

* Typical value

** EN 1815 replaces ISO 6356

Some of the collections are design protected.